

**EVOFIRE MIDI 92 TILTABLE FIRE RATED DOWNLIGHT IP20 70-85MM CUTOUT 92MM BEZEL WHITE ROUND +GU10 HOLDER INTEGRAL**

ILD LFR70K051



Introducing Integral’s new Evofire Midi 92 fire-rated tiltable downlight in white—for compact construction and seamless installation that doesn’t compromise on safety or affordability. With an ultra-thin 1mm ‘blend in’ bezel, this midi downlight is more discreet than ever and benefits from IP20 protection, making it the perfect choice for subtle lighting in dry indoor spaces like bedrooms and lounges. The fire-resistant glass and steel body forms a barrier below the ceiling for increased safety, while the push fit loop in/out connector makes installation a breeze. Direct light in your preferred direction with tiltable mechanism. Available with seven-year warranty for your peace of mind.

**Details**

<b>Barcode:</b>	5055788324546
<b>Quick Order Code:</b>	103651
<b>Category:</b>	Downlights
<b>Range Name:</b>	Evofire Midi 92
<b>Product Type:</b>	Fire Rated
<b>Product Body Finish:</b>	White
<b>Market Segment:</b>	Commercial indoor, Residential indoor
<b>Features:</b>	Tiltable, Without Insulation Guard
<b>Fixed/Tiltable:</b>	Tiltable
<b>Warranty (Years):</b>	7

**Physical Data**

<b>Product Depth (mm):</b>	38.5
<b>Product Weight (g):</b>	0.18
<b>Material:</b>	Steel, Glass
<b>Overall diameter (mm):</b>	92
<b>Construction:</b>	Pressed Steel, Glass
<b>Cut Out Diameter (mm):</b>	70-85
<b>Bulb or Luminaire Shape:</b>	Round
<b>Luminaire Fixing:</b>	Recess mounted
<b>Placement / Application:</b>	Indoor, General Lighting

**Electrical Data**

<b>Insulation Guard:</b>	No
--------------------------	----

<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes

## Light Data

<b>Fire Rating (mins):</b>	30, 60, 90
----------------------------	------------

## Environment

<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Back/Recessed side):</b>	IP20
<b>IP Rating (Ingress Protection):</b>	IP20
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	45

## Packaging

<b>Barcode:</b>	5055788324546
<b>Single box qty:</b>	1
<b>Package Weight (g):</b>	0.21
<b>Package Length (mm):</b>	105
<b>Package Width (mm):</b>	105
<b>Package Depth (mm):</b>	105
<b>Outer Carton Barcode:</b>	05055788324621
<b>Qty per Outer Carton:</b>	80
<b>Outer Carton Length (mm):</b>	440
<b>Outer Carton Width (mm):</b>	440
<b>Outer Carton Depth (mm):</b>	320
<b>Qty per euro pallet:</b>	1920